

DIGITAL MULTIMETER MY70 / MY74 / MY75



MY70

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



MY74

VOLTAGE AC 600V
AC 600V

CURRENT AC 10A
DC 10A



MY75

VOLTAGE AC 600V

CURRENT AC 10A
DC 10A



Specifications		MY70	MY74	MY75
Specifications	Range			
				Accuracy
DC Voltage	200mV			±(0.05%+3)
	2V/20V/200V			±(0.1%+3)
	200mV/2V/20V/200V	±(0.5%+3)	±(0.5%+3)	
AC Voltage	600V	±(0.8%+3)	±(0.8%+3)	±(0.15%+3)
	200mV	±(1.2%+3)		
	2V			±(0.5%+3)
DC Current	20V/200V	±(0.8%+3)	±(0.8%+3)	±(0.8%+10)
	200μA	±(2.0%+5)		
	2mA/20mA	±(0.8%+3)		±(0.5%+5)
AC Current	200mA			±(0.8%+5)
	2mA/20mA/200mA	±(1.5%+1)	±(1.5%+1)	
	10A	±(2.0%+5)	±(2.0%+5)	±(2.0%+10)
Resistance	20μA/200μA	±(1.8%+5)		
	2mA/20mA			±(0.8%+10)
	2mA/20mA/200mA	±(1.8%+5)	±(1.8%+5)	±(1.2%+10)
	10A	±(3.0%+5)	±(3.0%+5)	±(2.5%+10)
Capacitance	200Ω			±(0.5%+10)
	2KΩ/20KΩ/200KΩ/2MΩ			±(0.3%+3)
	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+3)	±(0.8%+3)	
	20MΩ	±(1.0%+5)	±(1.0%+5)	±(0.5%+1)
Frequency	200 MΩ	±(6.0%+10)	±(6.0%+10)	±(5.0%+10)
	2nF/20nF/200nF/2μF		±(4.0%+3)	±(4.0%+20)
Temperature(°C)	100μF		±(6.0%+10)	±(4.0%+20)
	20kHz		±(1.5%+5)	±(1.5%+5)
Features				
Display	counts	2000	2000	20000
Transistor hFE	0~1000	●	●	●
Diode	2.7V	●	●	●
Continuity Buzzer	<50Ω	●	●	●
Data Hold		●	●	●
Apo	Auto Power Off	●	●	●
LBD	Low Battery Display	●	●	●
General				
Power Supply	1×9V 6F22 Battery			
Product Size	195mm×95mm×55mm/7.67"×3.74"×2.16"			
Product Weight	366g/0.8lb			
Safety Rating	CE CAT III 600V RoHS			